

MR-68 and MR-88 Applications



Overview >>>

The MR-68 and MR-88 earth anchors can be used to install through

- Soil
- Asphalt
- Concrete

How It Works >>>




Drive Anchor



Remove Drive Steel



Pull Rod



Load Locked

Foresight Products LLC earth anchors work like a toggle bolt in soil. The Manta Ray® anchor is driven into the ground (with no digging) providing a safe and environmentally sensitive installation. An upward pull on the anchor tendon rotates the anchor into a perpendicular “anchor lock” position in undisturbed soil.

- No digging required
- No soil disturbance
- No concrete needed
- No drilling

Applications >>>

Ideal for:

- Benches
- Bleachers
- Tables
- Sheds
- Carports
- Flexible Curbing
- Parking Stops
- Trash Containers
- Planters
- Many other uses



Soil Installation

The MR-68 and MR-88 earth anchors can be used to install in soil

- Installs with ease with a small jack hammer or 10lb sledge
- Lock anchor manually, with farm jack or tested with LL-2 load locker



LL-2

Asphalt Installation

The MR-68 and MR-88 earth anchors can be used to install through asphalt

- Asphalt, No problem!
- Installs with ease
- No asphalt removal required



Concrete Installation

The MR-68 and MR-88 earth anchors can be used to install through concrete

- Core a 3" hole
- Install anchor through hole
- Pull up and lock into position
- Attach applicable hardware

(When finished, remove anchor rod if necessary)



Product Overview Chart >>>

Product	Description	Product	Description
MR-68	Anchor for use with 3/8"-16 rod	MR-88	Anchor for use with 1/2"-13 rod
MR-68-RA 1	Assembly including 3' x 3/8" rod, nut and washer	MR-88-RA 1	Assembly including 3'x1/2" rod, nut and washer
EN-12G	Eye nut for 3/8" rod	EN-16G	Eye nut for 1/2" rod
DS-68-HD	Hand drive steel for MR-68 anchors	DS-88	Hand drive steel for MR-88 anchors
PDS-6814	Power drive steel 4', 1 1/4" x 6" shank	PDS-8814	Power drive steel 4', 1 1/4" x 6" shank
PDS-6818	Power drive steel 4', 1 1/8" x 6" shank	PDS-8818	Power drive steel 4', 1 1/8" x 6" shank
LS-12-15	Locking socket for MR-68, 15"	LS-16-15	Locking socket for MR-88, 15"

*Additional assemblies available. Please inquire for details.

Contact us to learn more about Series II Earth Anchors

Toll Free: 800-325-5360 | Local: 303-286-8955 | Fax: 303-287-3866
sales@earthanchor.com | www.earthanchor.com



6430 East 49th Drive, Commerce City, CO 80022 USA